

## QN0603X104J3950FB

R25=100kΩ±5%， B25/50=3950±1%， B25/85=3987

温度 Temp. (°C)	R 最小值 R_Min (Kohm)	R 中心值 R_Cent (Kohm)	R 最大值 R_Max (Kohm)	阻值公差 Res TOL.	温度公差 Temp. TOL.(°C)
-40	3,165.970	3,452.748	3,756.089	8.79%	1.26
-39	2,961.799	3,227.909	3,509.132	8.71%	1.26
-38	2,772.192	3,019.247	3,280.099	8.64%	1.26
-37	2,596.014	2,825.494	3,067.571	8.57%	1.26
-36	2,432.227	2,645.486	2,870.251	8.50%	1.26
-35	2,279.879	2,478.161	2,686.954	8.43%	1.26
-34	2,138.098	2,322.542	2,516.591	8.35%	1.26
-33	2,006.083	2,177.736	2,358.168	8.29%	1.26
-32	1,883.098	2,042.922	2,210.770	8.22%	1.26
-31	1,768.468	1,917.347	2,073.562	8.15%	1.25
-30	1,661.574	1,800.319	1,945.773	8.08%	1.25
-29	1,561.843	1,691.203	1,826.699	8.01%	1.25
-28	1,468.751	1,589.414	1,715.689	7.94%	1.25
-27	1,381.814	1,494.413	1,612.147	7.88%	1.25
-26	1,300.587	1,405.707	1,515.525	7.81%	1.25
-25	1,224.660	1,322.839	1,425.317	7.75%	1.25
-24	1,153.501	1,245.222	1,340.876	7.68%	1.25
-23	1,086.938	1,172.662	1,261.984	7.62%	1.25
-22	1,024.646	1,104.798	1,188.242	7.55%	1.24
-21	966.324	1,041.298	1,119.284	7.49%	1.24
-20	911.696	981.854	1,054.767	7.43%	1.24
-19	860.504	926.182	994.381	7.36%	1.24
-18	812.512	874.020	937.834	7.30%	1.24
-17	767.500	825.125	884.860	7.24%	1.24
-16	725.265	779.274	835.211	7.18%	1.24
-15	685.619	736.257	788.658	7.12%	1.23
-14	648.387	695.883	744.991	7.06%	1.23

温度 Temp. (°C)	R 最小值 R_Min (Kohm)	R 中心值 R_Cent (Kohm)	R 最大值 R_Max (Kohm)	阻值公差 Res TOL.	温度公差 Temp. TOL.(°C)
-13	613.409	657.974	704.012	7.00%	1.23
-12	580.535	622.365	665.541	6.94%	1.23
-11	549.625	588.902	629.409	6.88%	1.23
-10	520.551	557.444	595.460	6.82%	1.23
-9	493.192	527.858	563.549	6.76%	1.22
-8	467.437	500.023	533.542	6.70%	1.22
-7	443.184	473.824	505.315	6.65%	1.22
-6	420.336	449.155	478.751	6.59%	1.22
-5	398.803	425.920	453.744	6.53%	1.22
-4	378.474	403.995	430.160	6.48%	1.21
-3	359.305	383.332	407.944	6.42%	1.21
-2	341.222	363.850	387.009	6.36%	1.21
-1	324.158	345.475	367.274	6.31%	1.21
0	308.049	328.139	348.664	6.26%	1.21
1	292.854	311.793	331.127	6.20%	1.20
2	278.497	296.357	314.574	6.15%	1.20
3	264.928	281.775	298.945	6.09%	1.20
4	252.098	267.995	284.183	6.04%	1.20
5	239.964	254.969	270.235	5.99%	1.19
6	228.462	242.628	257.027	5.93%	1.19
7	217.580	230.956	244.543	5.88%	1.19
8	207.280	219.915	232.738	5.83%	1.19
9	197.528	209.467	221.572	5.78%	1.18
10	188.291	199.576	211.008	5.73%	1.18
11	179.547	190.215	201.015	5.68%	1.18
12	171.258	181.348	191.552	5.63%	1.18
13	163.398	172.943	182.588	5.58%	1.17
14	155.944	164.976	174.094	5.53%	1.17
15	148.872	157.420	166.043	5.48%	1.17
16	142.158	150.250	158.407	5.43%	1.16

温度 Temp. (°C)	R 最小值 R_Min (Kohm)	R 中心值 R_Cent (Kohm)	R 最大值 R_Max (Kohm)	阻值公差 Res TOL.	温度公差 Temp. TOL.(°C)
17	135.785	143.448	151.165	5.38%	1.16
18	129.732	136.991	144.294	5.33%	1.16
19	123.985	130.862	137.775	5.28%	1.15
20	118.524	125.041	131.587	5.23%	1.15
21	113.334	119.511	125.711	5.19%	1.15
22	108.400	114.257	120.130	5.14%	1.15
23	103.709	109.264	114.829	5.09%	1.14
24	99.246	104.515	109.790	5.05%	1.14
25	95.000	100.000	105.000	5.00%	1.14
26	90.879	95.704	100.533	5.05%	1.15
27	86.960	91.617	96.282	5.09%	1.17
28	83.231	87.726	92.233	5.14%	1.19
29	79.681	84.021	88.376	5.18%	1.21
30	76.303	80.493	84.701	5.23%	1.22
31	73.087	77.133	81.200	5.27%	1.24
32	70.024	73.932	77.864	5.32%	1.26
33	67.106	70.881	74.682	5.36%	1.28
34	64.325	67.973	71.647	5.41%	1.30
35	61.675	65.199	68.752	5.45%	1.32
36	59.148	62.554	65.990	5.49%	1.34
37	56.738	60.030	63.354	5.54%	1.35
38	54.439	57.621	60.837	5.58%	1.37
39	52.246	55.322	58.433	5.62%	1.39
40	50.153	53.127	56.138	5.67%	1.41
41	48.154	51.030	53.944	5.71%	1.43
42	46.246	49.028	51.848	5.75%	1.45
43	44.423	47.115	49.844	5.79%	1.47
44	42.682	45.285	47.928	5.84%	1.49
45	41.018	43.537	46.096	5.88%	1.51
46	39.429	41.867	44.345	5.92%	1.53

温度 Temp. (°C)	R 最小值 R_Min (Kohm)	R 中心值 R_Cent (Kohm)	R 最大值 R_Max (Kohm)	阻值公差 Res TOL.	温度公差 Temp. TOL.(°C)
47	37.911	40.270	42.670	5.96%	1.55
48	36.458	38.743	41.067	6.00%	1.57
49	35.069	37.281	39.533	6.04%	1.59
50	33.740	35.882	38.064	6.08%	1.61
51	32.469	34.543	36.657	6.12%	1.63
52	31.252	33.260	35.310	6.16%	1.65
53	30.086	32.032	34.019	6.20%	1.67
54	28.970	30.856	32.782	6.24%	1.69
55	27.902	29.729	31.596	6.28%	1.71
56	26.878	28.649	30.459	6.32%	1.73
57	25.897	27.613	29.369	6.36%	1.75
58	24.957	26.620	28.324	6.40%	1.77
59	24.056	25.669	27.321	6.44%	1.79
60	23.192	24.755	26.359	6.48%	1.81
61	22.364	23.881	25.437	6.51%	1.84
62	21.571	23.042	24.552	6.55%	1.86
63	20.810	22.237	23.702	6.59%	1.88
64	20.079	21.464	22.886	6.63%	1.90
65	19.378	20.721	22.103	6.67%	1.92
66	18.703	20.007	21.348	6.70%	1.94
67	18.056	19.321	20.623	6.74%	1.96
68	17.433	18.661	19.926	6.78%	1.99
69	16.835	18.028	19.256	6.81%	2.01
70	16.261	17.419	18.612	6.85%	2.03
71	15.712	16.836	17.996	6.89%	2.05
72	15.184	16.276	17.403	6.92%	2.08
73	14.677	15.738	16.833	6.96%	2.10
74	14.189	15.220	16.284	7.00%	2.12
75	13.720	14.721	15.756	7.03%	2.14
76	13.267	14.240	15.247	7.07%	2.17

温度 Temp. (°C)	R 最小值 R_Min (Kohm)	R 中心值 R_Cent (Kohm)	R 最大值 R_Max (Kohm)	阻值公差 Res TOL.	温度公差 Temp. TOL.(°C)
77	12.832	13.777	14.756	7.10%	2.19
78	12.413	13.332	14.283	7.14%	2.21
79	12.009	12.903	13.828	7.17%	2.23
80	11.621	12.490	13.390	7.21%	2.26
81	11.248	12.093	12.969	7.24%	2.28
82	10.889	11.711	12.563	7.28%	2.30
83	10.544	11.343	12.172	7.31%	2.33
84	10.211	10.988	11.795	7.34%	2.35
85	9.890	10.646	11.431	7.38%	2.37
86	9.580	10.316	11.081	7.41%	2.40
87	9.282	9.999	10.743	7.45%	2.42
88	8.995	9.692	10.417	7.48%	2.45
89	8.718	9.396	10.102	7.51%	2.47
90	8.450	9.111	9.798	7.55%	2.49
91	8.193	8.836	9.506	7.58%	2.52
92	7.944	8.570	9.223	7.61%	2.54
93	7.704	8.314	8.950	7.64%	2.57
94	7.473	8.066	8.686	7.68%	2.59
95	7.249	7.828	8.431	7.71%	2.62
96	7.034	7.598	8.186	7.74%	2.64
97	6.827	7.376	7.949	7.77%	2.67
98	6.627	7.162	7.721	7.81%	2.69
99	6.433	6.955	7.500	7.84%	2.72
100	6.246	6.755	7.286	7.87%	2.74
101	6.066	6.561	7.080	7.90%	2.77
102	5.891	6.374	6.880	7.93%	2.79
103	5.723	6.194	6.687	7.96%	2.82
104	5.559	6.019	6.500	7.99%	2.84
105	5.402	5.850	6.319	8.02%	2.87
106	5.249	5.686	6.144	8.05%	2.89

温度 Temp. (°C)	R 最小值 R_Min (Kohm)	R 中心值 R_Cent (Kohm)	R 最大值 R_Max (Kohm)	阻值公差 Res TOL.	温度公差 Temp. TOL.(°C)
107	5.102	5.528	5.975	8.08%	2.92
108	4.960	5.375	5.812	8.11%	2.95
109	4.821	5.227	5.653	8.15%	2.97
110	4.688	5.084	5.500	8.18%	3.00
111	4.559	4.945	5.351	8.21%	3.02
112	4.434	4.811	5.207	8.23%	3.05
113	4.313	4.681	5.068	8.26%	3.08
114	4.196	4.555	4.933	8.29%	3.10
115	4.082	4.433	4.802	8.32%	3.13
116	3.973	4.316	4.676	8.35%	3.16
117	3.867	4.202	4.554	8.38%	3.18
118	3.765	4.092	4.436	8.41%	3.21
119	3.666	3.985	4.321	8.44%	3.24
120	3.569	3.881	4.210	8.47%	3.26
121	3.476	3.781	4.102	8.50%	3.29
122	3.386	3.684	3.998	8.52%	3.32
123	3.298	3.589	3.896	8.55%	3.35
124	3.213	3.498	3.798	8.58%	3.37
125	3.131	3.409	3.703	8.61%	3.40