

## QN0805X224J3950FB

R25=220kΩ±5%， B25/50=3950±1%， B25/85=3987

温度 Temp. (°C)	R 最小值 R_Min (Kohm)	R 中心值 R_Cent (Kohm)	R 最大值 R_Max (Kohm)	阻值公差 Res TOL.	温度公差 Temp. TOL.(°C)
-40	6,965.135	7596.046	8,263.395	8.79%	1.26
-39	6,515.958	7101.399	7,720.091	8.71%	1.26
-38	6,098.822	6642.344	7,216.218	8.64%	1.26
-37	5,711.230	6216.086	6,748.655	8.57%	1.26
-36	5,350.899	5820.070	6,314.552	8.50%	1.26
-35	5,015.735	5451.955	5,911.298	8.43%	1.26
-34	4,703.815	5109.593	5,536.499	8.35%	1.26
-33	4,413.382	4791.020	5,187.969	8.29%	1.26
-32	4,142.815	4494.428	4,863.694	8.22%	1.26
-31	3,890.630	4218.163	4,561.836	8.15%	1.25
-30	3,655.462	3960.702	4,280.702	8.08%	1.25
-29	3,436.054	3720.646	4,018.737	8.01%	1.25
-28	3,231.252	3496.710	3,774.516	7.94%	1.25
-27	3,039.991	3287.709	3,546.724	7.88%	1.25
-26	2,861.292	3092.556	3,334.155	7.81%	1.25
-25	2,694.252	2910.246	3,135.697	7.75%	1.25
-24	2,537.702	2739.488	2,949.926	7.68%	1.25
-23	2,391.263	2579.856	2,776.365	7.62%	1.25
-22	2,254.221	2430.556	2,614.133	7.55%	1.24
-21	2,125.914	2290.856	2,462.424	7.49%	1.24
-20	2,005.731	2160.079	2,320.488	7.43%	1.24
-19	1,893.110	2037.601	2,187.638	7.36%	1.24
-18	1,787.526	1922.844	2,063.234	7.30%	1.24
-17	1,688.500	1815.276	1,946.692	7.24%	1.24
-16	1,595.583	1714.402	1,837.464	7.18%	1.24
-15	1,508.361	1619.765	1,735.048	7.12%	1.23
-14	1,426.452	1530.943	1,638.980	7.06%	1.23

温度 Temp. (°C)	R 最小值 R_Min (Kohm)	R 中心值 R_Cent (Kohm)	R 最大值 R_Max (Kohm)	阻值公差 Res TOL.	温度公差 Temp. TOL.(°C)
-13	1,349.500	1447.543	1,548.827	7.00%	1.23
-12	1,277.177	1369.203	1,464.191	6.94%	1.23
-11	1,209.175	1295.585	1,384.700	6.88%	1.23
-10	1,145.211	1226.377	1,310.012	6.82%	1.23
-9	1,085.022	1161.288	1,239.808	6.76%	1.22
-8	1,028.362	1100.050	1,173.793	6.70%	1.22
-7	975.005	1042.412	1,111.693	6.65%	1.22
-6	924.739	988.142	1,053.253	6.59%	1.22
-5	877.366	937.024	998.236	6.53%	1.22
-4	832.643	888.790	946.351	6.48%	1.21
-3	790.471	843.331	897.477	6.42%	1.21
-2	750.689	800.471	851.421	6.36%	1.21
-1	713.147	760.046	808.004	6.31%	1.21
0	677.709	721.905	767.061	6.26%	1.21
1	644.279	685.945	728.479	6.20%	1.20
2	612.694	651.986	692.063	6.15%	1.20
3	582.841	619.906	657.679	6.09%	1.20
4	554.616	589.590	625.202	6.04%	1.20
5	527.920	560.931	594.516	5.99%	1.19
6	502.617	533.781	565.460	5.93%	1.19
7	478.675	508.104	537.994	5.88%	1.19
8	456.015	483.814	512.024	5.83%	1.19
9	434.561	460.827	487.459	5.78%	1.18
10	414.241	439.067	464.217	5.73%	1.18
11	395.002	418.474	442.232	5.68%	1.18
12	376.767	398.965	421.414	5.63%	1.18
13	359.477	380.475	401.693	5.58%	1.17
14	343.078	362.947	383.007	5.53%	1.17
15	327.519	346.325	365.295	5.48%	1.17
16	312.748	330.551	348.495	5.43%	1.16

温度 Temp. (°C)	R 最小值 R_Min (Kohm)	R 中心值 R_Cent (Kohm)	R 最大值 R_Max (Kohm)	阻值公差 Res TOL.	温度公差 Temp. TOL.(°C)
17	298.726	315.585	332.562	5.38%	1.16
18	285.411	301.380	317.447	5.33%	1.16
19	272.767	287.896	303.105	5.28%	1.15
20	260.752	275.090	289.491	5.23%	1.15
21	249.334	262.925	276.564	5.19%	1.15
22	238.480	251.366	264.286	5.14%	1.15
23	228.159	240.380	252.623	5.09%	1.14
24	218.341	229.934	241.537	5.05%	1.14
25	209.000	220.000	231.000	5.00%	1.14
26	199.934	210.549	221.174	5.05%	1.15
27	191.312	201.557	211.820	5.09%	1.17
28	183.107	192.997	202.912	5.14%	1.19
29	175.299	184.847	194.428	5.18%	1.21
30	167.866	177.085	186.343	5.23%	1.22
31	160.790	169.693	178.641	5.27%	1.24
32	154.052	162.651	171.300	5.32%	1.26
33	147.633	155.939	164.300	5.36%	1.28
34	141.516	149.540	157.624	5.41%	1.30
35	135.685	143.438	151.255	5.45%	1.32
36	130.125	137.618	145.178	5.49%	1.34
37	124.824	132.066	139.379	5.54%	1.35
38	119.767	126.767	133.841	5.58%	1.37
39	114.941	121.709	128.553	5.62%	1.39
40	110.336	116.880	123.503	5.67%	1.41
41	105.939	112.267	118.676	5.71%	1.43
42	101.741	107.862	114.065	5.75%	1.45
43	97.731	103.652	109.657	5.79%	1.47
44	93.900	99.628	105.441	5.84%	1.49
45	90.239	95.782	101.411	5.88%	1.51
46	86.744	92.108	97.559	5.92%	1.53

温度 Temp. (°C)	R 最小值 R_Min (Kohm)	R 中心值 R_Cent (Kohm)	R 最大值 R_Max (Kohm)	阻值公差 Res TOL.	温度公差 Temp. TOL.(°C)
47	83.403	88.595	93.875	5.96%	1.55
48	80.208	85.234	90.348	6.00%	1.57
49	77.152	82.018	86.973	6.04%	1.59
50	74.228	78.940	83.741	6.08%	1.61
51	71.431	75.994	80.646	6.12%	1.63
52	68.753	73.173	77.682	6.16%	1.65
53	66.190	70.471	74.842	6.20%	1.67
54	63.735	67.883	72.120	6.24%	1.69
55	61.384	65.403	69.511	6.28%	1.71
56	59.132	63.027	67.011	6.32%	1.73
57	56.974	60.749	64.613	6.36%	1.75
58	54.905	58.565	62.313	6.40%	1.77
59	52.923	56.471	60.106	6.44%	1.79
60	51.022	54.462	57.989	6.48%	1.81
61	49.201	52.538	55.961	6.51%	1.84
62	47.456	50.692	54.014	6.55%	1.86
63	45.781	48.921	52.145	6.59%	1.88
64	44.174	47.220	50.350	6.63%	1.90
65	42.631	45.587	48.626	6.67%	1.92
66	41.147	44.015	46.965	6.70%	1.94
67	39.722	42.506	45.371	6.74%	1.96
68	38.353	41.055	43.838	6.78%	1.99
69	37.038	39.661	42.364	6.81%	2.01
70	35.774	38.321	40.946	6.85%	2.03
71	34.567	37.040	39.591	6.89%	2.05
72	33.406	35.808	38.287	6.92%	2.08
73	32.289	34.623	37.033	6.96%	2.10
74	31.216	33.483	35.825	7.00%	2.12
75	30.184	32.387	34.664	7.03%	2.14
76	29.188	31.329	33.543	7.07%	2.17

温度 Temp. (°C)	R 最小值 R_Min (Kohm)	R 中心值 R_Cent (Kohm)	R 最大值 R_Max (Kohm)	阻值公差 Res TOL.	温度公差 Temp. TOL.(°C)
77	28.229	30.310	32.463	7.10%	2.19
78	27.308	29.330	31.423	7.14%	2.21
79	26.420	28.386	30.422	7.17%	2.23
80	25.566	27.477	29.457	7.21%	2.26
81	24.746	26.605	28.532	7.24%	2.28
82	23.956	25.764	27.639	7.28%	2.30
83	23.196	24.954	26.778	7.31%	2.33
84	22.464	24.174	25.949	7.34%	2.35
85	21.757	23.421	25.149	7.38%	2.37
86	21.077	22.696	24.378	7.41%	2.40
87	20.421	21.997	23.635	7.45%	2.42
88	19.789	21.322	22.917	7.48%	2.45
89	19.179	20.672	22.225	7.51%	2.47
90	18.591	20.044	21.556	7.55%	2.49
91	18.024	19.439	20.912	7.58%	2.52
92	17.478	18.855	20.290	7.61%	2.54
93	16.950	18.291	19.689	7.64%	2.57
94	16.440	17.746	19.108	7.68%	2.59
95	15.948	17.221	18.549	7.71%	2.62
96	15.475	16.715	18.009	7.74%	2.64
97	15.019	16.227	17.488	7.77%	2.67
98	14.579	15.756	16.986	7.81%	2.69
99	14.153	15.300	16.499	7.84%	2.72
100	13.742	14.860	16.029	7.87%	2.74
101	13.345	14.435	15.575	7.90%	2.77
102	12.960	14.023	15.135	7.93%	2.79
103	12.590	13.626	14.711	7.96%	2.82
104	12.230	13.241	14.299	7.99%	2.84
105	11.884	12.870	13.903	8.02%	2.87
106	11.549	12.510	13.518	8.05%	2.89

温度 Temp. (°C)	R 最小值 R_Min (Kohm)	R 中心值 R_Cent (Kohm)	R 最大值 R_Max (Kohm)	阻值公差 Res TOL.	温度公差 Temp. TOL.(°C)
107	11.224	12.162	13.145	8.08%	2.92
108	10.911	11.826	12.786	8.11%	2.95
109	10.607	11.500	12.437	8.15%	2.97
110	10.314	11.185	12.099	8.18%	3.00
111	10.029	10.879	11.772	8.21%	3.02
112	9.754	10.584	11.456	8.23%	3.05
113	9.488	10.298	11.149	8.26%	3.08
114	9.230	10.021	10.852	8.29%	3.10
115	8.981	9.753	10.565	8.32%	3.13
116	8.741	9.495	10.288	8.35%	3.16
117	8.508	9.244	10.019	8.38%	3.18
118	8.283	9.002	9.759	8.41%	3.21
119	8.065	8.767	9.507	8.44%	3.24
120	7.853	8.539	9.262	8.47%	3.26
121	7.647	8.318	9.025	8.50%	3.29
122	7.449	8.104	8.795	8.52%	3.32
123	7.256	7.896	8.571	8.55%	3.35
124	7.069	7.695	8.355	8.58%	3.37
125	6.888	7.500	8.146	8.61%	3.40