

QN0805X334J3950FB

R25=330kΩ±5%， B25/50=3950±1%， B25/85=3987

温度 Temp. (°C)	R 最小值 R_Min (Kohm)	R 中心值 R_Cent (Kohm)	R 最大值 R_Max (Kohm)	阻值公差 Res TOL.	温度公差 Temp. TOL.(°C)
-40	10,447.703	11,394.069	12,395.093	8.79%	1.26
-39	9,773.938	10,652.099	11,580.137	8.71%	1.26
-38	9,148.233	9,963.516	10,824.327	8.64%	1.26
-37	8,566.846	9,324.129	10,122.983	8.57%	1.26
-36	8,026.349	8,730.105	9,471.828	8.50%	1.26
-35	7,523.602	8,177.933	8,866.947	8.43%	1.26
-34	7,055.723	7,664.390	8,304.749	8.35%	1.26
-33	6,620.073	7,186.530	7,781.953	8.29%	1.26
-32	6,214.222	6,741.642	7,295.541	8.22%	1.26
-31	5,835.945	6,327.245	6,842.754	8.15%	1.25
-30	5,483.193	5,941.053	6,421.052	8.08%	1.25
-29	5,154.081	5,580.969	6,028.106	8.01%	1.25
-28	4,846.878	5,245.065	5,661.774	7.94%	1.25
-27	4,559.986	4,931.564	5,320.086	7.88%	1.25
-26	4,291.938	4,638.834	5,001.233	7.81%	1.25
-25	4,041.378	4,365.369	4,703.545	7.75%	1.25
-24	3,806.552	4,109.232	4,424.889	7.68%	1.25
-23	3,586.894	3,869.784	4,164.547	7.62%	1.25
-22	3,381.331	3,645.834	3,921.200	7.55%	1.24
-21	3,188.871	3,436.284	3,693.636	7.49%	1.24
-20	3,008.597	3,240.119	3,480.733	7.43%	1.24
-19	2,839.665	3,056.402	3,281.457	7.36%	1.24
-18	2,681.289	2,884.266	3,094.852	7.30%	1.24
-17	2,532.750	2,722.914	2,920.037	7.24%	1.24
-16	2,393.374	2,571.603	2,756.196	7.18%	1.24
-15	2,262.542	2,429.648	2,602.573	7.12%	1.23
-14	2,139.678	2,296.415	2,458.470	7.06%	1.23

温度 Temp. (°C)	R 最小值 R_Min (Kohm)	R 中心值 R_Cent (Kohm)	R 最大值 R_Max (Kohm)	阻值公差 Res TOL.	温度公差 Temp. TOL.(°C)
-13	2,024.250	2,171.315	2,323.240	7.00%	1.23
-12	1,915.765	2,053.805	2,196.286	6.94%	1.23
-11	1,813.762	1,943.378	2,077.050	6.88%	1.23
-10	1,717.817	1,839.566	1,965.018	6.82%	1.23
-9	1,627.532	1,741.932	1,859.712	6.76%	1.22
-8	1,542.543	1,650.075	1,760.690	6.70%	1.22
-7	1,462.507	1,563.618	1,667.539	6.65%	1.22
-6	1,387.108	1,482.213	1,579.879	6.59%	1.22
-5	1,316.050	1,405.536	1,497.354	6.53%	1.22
-4	1,248.965	1,333.185	1,419.526	6.48%	1.21
-3	1,185.706	1,264.997	1,346.215	6.42%	1.21
-2	1,126.033	1,200.707	1,277.131	6.36%	1.21
-1	1,069.721	1,140.069	1,212.006	6.31%	1.21
0	1,016.563	1,082.858	1,150.592	6.26%	1.21
1	966.419	1,028.918	1,092.719	6.20%	1.20
2	919.041	977.979	1,038.095	6.15%	1.20
3	874.262	929.859	986.519	6.09%	1.20
4	831.924	884.385	937.804	6.04%	1.20
5	791.880	841.397	891.774	5.99%	1.19
6	753.926	800.672	848.190	5.93%	1.19
7	718.013	762.156	806.991	5.88%	1.19
8	684.023	725.721	768.036	5.83%	1.19
9	651.841	691.241	731.189	5.78%	1.18
10	621.362	658.601	696.326	5.73%	1.18
11	592.503	627.711	663.348	5.68%	1.18
12	565.151	598.448	632.121	5.63%	1.18
13	539.215	570.713	602.540	5.58%	1.17
14	514.617	544.421	574.511	5.53%	1.17
15	491.279	519.488	547.943	5.48%	1.17
16	469.121	495.827	522.742	5.43%	1.16

温度 Temp. (°C)	R 最小值 R_Min (Kohm)	R 中心值 R_Cent (Kohm)	R 最大值 R_Max (Kohm)	阻值公差 Res TOL.	温度公差 Temp. TOL.(°C)
17	448.089	473.378	498.843	5.38%	1.16
18	428.117	452.070	476.170	5.33%	1.16
19	409.150	431.844	454.657	5.28%	1.15
20	391.128	412.635	434.236	5.23%	1.15
21	374.001	394.388	414.846	5.19%	1.15
22	357.719	377.049	396.429	5.14%	1.15
23	342.238	360.570	378.934	5.09%	1.14
24	327.511	344.901	362.306	5.05%	1.14
25	313.500	330.000	346.500	5.00%	1.14
26	299.901	315.824	331.760	5.05%	1.15
27	286.967	302.336	317.730	5.09%	1.17
28	274.661	289.496	304.369	5.14%	1.19
29	262.949	277.271	291.641	5.18%	1.21
30	251.799	265.628	279.515	5.23%	1.22
31	241.186	254.540	267.961	5.27%	1.24
32	231.079	243.977	256.950	5.32%	1.26
33	221.450	233.909	246.451	5.36%	1.28
34	212.273	224.310	236.437	5.41%	1.30
35	203.527	215.157	226.883	5.45%	1.32
36	195.188	206.427	217.768	5.49%	1.34
37	187.236	198.099	209.068	5.54%	1.35
38	179.650	190.151	200.762	5.58%	1.37
39	172.412	182.564	192.830	5.62%	1.39
40	165.504	175.320	185.254	5.67%	1.41
41	158.908	168.401	178.014	5.71%	1.43
42	152.612	161.793	171.098	5.75%	1.45
43	146.597	155.478	164.485	5.79%	1.47
44	140.850	149.442	158.162	5.84%	1.49
45	135.359	143.673	152.116	5.88%	1.51
46	130.116	138.162	146.339	5.92%	1.53

温度 Temp. (°C)	R 最小值 R_Min (Kohm)	R 中心值 R_Cent (Kohm)	R 最大值 R_Max (Kohm)	阻值公差 Res TOL.	温度公差 Temp. TOL.(°C)
47	125.105	132.893	140.812	5.96%	1.55
48	120.312	127.851	135.523	6.00%	1.57
49	115.728	123.027	130.459	6.04%	1.59
50	111.342	118.410	125.611	6.08%	1.61
51	107.146	113.991	120.970	6.12%	1.63
52	103.130	109.760	116.523	6.16%	1.65
53	99.284	105.707	112.263	6.20%	1.67
54	95.603	101.825	108.180	6.24%	1.69
55	92.076	98.105	104.267	6.28%	1.71
56	88.698	94.541	100.516	6.32%	1.73
57	85.460	91.124	96.919	6.36%	1.75
58	82.358	87.848	93.469	6.40%	1.77
59	79.384	84.707	90.160	6.44%	1.79
60	76.532	81.693	86.984	6.48%	1.81
61	73.802	78.807	83.941	6.51%	1.84
62	71.184	76.038	81.020	6.55%	1.86
63	68.672	73.382	78.218	6.59%	1.88
64	66.261	70.830	75.525	6.63%	1.90
65	63.947	68.381	72.939	6.67%	1.92
66	61.720	66.023	70.448	6.70%	1.94
67	59.583	63.759	68.057	6.74%	1.96
68	57.529	61.583	65.756	6.78%	1.99
69	55.557	59.492	63.546	6.81%	2.01
70	53.661	57.482	61.420	6.85%	2.03
71	51.850	55.560	59.387	6.89%	2.05
72	50.108	53.712	57.431	6.92%	2.08
73	48.434	51.935	55.549	6.96%	2.10
74	46.823	50.225	53.738	7.00%	2.12
75	45.276	48.581	51.996	7.03%	2.14
76	43.782	46.994	50.314	7.07%	2.17

温度 Temp. (°C)	R 最小值 R_Min (Kohm)	R 中心值 R_Cent (Kohm)	R 最大值 R_Max (Kohm)	阻值公差 Res TOL.	温度公差 Temp. TOL.(°C)
77	42.344	45.465	48.694	7.10%	2.19
78	40.961	43.995	47.135	7.14%	2.21
79	39.630	42.579	45.633	7.17%	2.23
80	38.349	41.216	44.186	7.21%	2.26
81	37.120	39.908	42.798	7.24%	2.28
82	35.935	38.646	41.458	7.28%	2.30
83	34.794	37.431	40.167	7.31%	2.33
84	33.696	36.261	38.924	7.34%	2.35
85	32.636	35.132	37.724	7.38%	2.37
86	31.615	34.044	36.567	7.41%	2.40
87	30.632	32.996	35.452	7.45%	2.42
88	29.683	31.983	34.375	7.48%	2.45
89	28.769	31.008	33.338	7.51%	2.47
90	27.887	30.066	32.335	7.55%	2.49
91	27.037	29.159	31.368	7.58%	2.52
92	26.216	28.283	30.435	7.61%	2.54
93	25.424	27.437	29.534	7.64%	2.57
94	24.659	26.619	28.663	7.68%	2.59
95	23.923	25.832	27.823	7.71%	2.62
96	23.213	25.073	27.013	7.74%	2.64
97	22.528	24.341	26.233	7.77%	2.67
98	21.868	23.634	25.479	7.81%	2.69
99	21.229	22.950	24.749	7.84%	2.72
100	20.612	22.290	24.044	7.87%	2.74
101	20.017	21.653	23.363	7.90%	2.77
102	19.440	21.035	22.703	7.93%	2.79
103	18.884	20.439	22.066	7.96%	2.82
104	18.346	19.862	21.449	7.99%	2.84
105	17.826	19.305	20.854	8.02%	2.87
106	17.323	18.765	20.276	8.05%	2.89

温度 Temp. (°C)	R 最小值 R_Min (Kohm)	R 中心值 R_Cent (Kohm)	R 最大值 R_Max (Kohm)	阻值公差 Res TOL.	温度公差 Temp. TOL.(°C)
107	16.836	18.243	19.718	8.08%	2.92
108	16.367	17.739	19.178	8.11%	2.95
109	15.911	17.250	18.655	8.15%	2.97
110	15.471	16.778	18.149	8.18%	3.00
111	15.043	16.319	17.657	8.21%	3.02
112	14.631	15.876	17.183	8.23%	3.05
113	14.232	15.447	16.724	8.26%	3.08
114	13.846	15.032	16.278	8.29%	3.10
115	13.472	14.630	15.847	8.32%	3.13
116	13.112	14.243	15.432	8.35%	3.16
117	12.762	13.866	15.028	8.38%	3.18
118	12.424	13.503	14.639	8.41%	3.21
119	12.097	13.151	14.260	8.44%	3.24
120	11.779	12.809	13.893	8.47%	3.26
121	11.471	12.477	13.537	8.50%	3.29
122	11.173	12.156	13.192	8.52%	3.32
123	10.884	11.844	12.857	8.55%	3.35
124	10.604	11.543	12.533	8.58%	3.37
125	10.332	11.250	12.218	8.61%	3.40